

ATF DMM DIII

Product Data Sheet | Art.no 4A211

Description

High-quality, automatic transmission oil for automatic gearboxes, power steering systems and torque converters for which a DIII oil is prescribed.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Colour	red
Density at 15 °C, g/ml	0.855
Kinematic viscosity at 40 °C, mm ² /s	33,9
Kinematic viscosity at 100 °C, mm ² /s	7,1
Viscosity index	179
Pour point, °C	-45
Brookfield viscosity at -40°C, mPa.s	17500
Flash Point COC, °C	196

Performance level

Allison C4
Ford Mercon
GM 6417-M DEXRON III -G
MAN 339 V1/Z1
MB 236.5/236.9
VOITH H55.6335xx
Volvo STD 1273,40 (97340)/1273,41 (97341)
ZF TE-ML 03D/04D/09/11B/14A/17C

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms