

Bio Grease M2 HT

Product Data Sheet | Art.no 24.106EP2

Description

Biodegradable, universally applicable grease. Highly water resistant, strong adhesive properties and extremely good anti-corrosion capacity. Suitable for heavy duty bearings, dowels, bushings, chassis points, ball joints, etc.



Instructions for use

Avoid spillages due to excessive grease usage. Seal the packaging properly after use. Do not mix with other types of grease. The safety information sheet for this product is available on request or can be downloaded directly via the website.

Available in



400g



18kg



50kg

Performance level

ISO 12924: L-XB(F)BIB2

DIN 51502: KPE2E-20

Swedish Standard 155470

Typical standard analyses

Colour	Yellow
NLGI class	2
Base oil type	Natural ester / Polymer / Vegetable oil
Base oil viscosity at 40°C	130
Penetration at 60W	265 - 295
Dropping point, °C	> 140 °C
Temperature range, °C	-20 to 90
4-ball weld load	2800
Emcor salt water	< 2 - 2
Water resistance 90 °C	0
	100
Renewable carbon content	93%

Bio Grease M2 HT

Product Data Sheet | Art.no 24.106EP2

Date printed 31-03-2025

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: gelders.nl/terms-and-conditions