

Chainsaw BIO

Product Data Sheet | Art.no 4B027

Description

High-quality, bio-degradable oil for lubricating the chains and saw systems of chain saws. Special additives prevent the oil spraying off either at low or high temperatures, and provide excellent protection against wear and corrosion.



Available in



1L



5L



25L



60L



208L



1000L

Application

For lubricating the chain, nose wheel and saw blade of petrol and electric chain saws. DO NOT use for lubricating the motor.

Typical standard analyses

Density at 15 °C, kg/l	0,917
Viscosity 40 °C, mm ² /s	68,00
Viscosity 100 °C, mm ² /s	14,30
Viscosity index	238
Flash Point COC, °C	322
Pour Point, °C	-21

Instructions for use

Check the oil level regularly. Avoid spillage when filling.

Performance level

Biodegradability according OECD 301B > 75 %

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms