

Chainsaw XF

Product Data Sheet | Art.no 4B028

Description

Chainsaw oil. Good adhesion to the chain, preventing oil spatter. Excellent lubricant properties. NB: chainsaw oil is not suitable for lubricating the power unit!



Available in



1L



5L



25L



60L



208L



1000L



Bulk

Typical standard analyses

Kinematic viscosity at 40 °C, mm ² /s	150
Flash Point COC, °C	>180
Texture	Stringy

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE
OIL FOR PROFESSIONALS