

# Cutting Oil

Product Data Sheet | Art.no 27.003

## Description

Non-emulsifying cutting oil. Use pure and undiluted. Suitable for all complex metalworking such as threadcutting, sawing, milling and deep drawing.



## Available in



1L



5L



20L



60L



208L

## Typical standard analyses

Appearance	Clear, bright yellow liquid
Density at 15 °C	887 kg/m <sup>3</sup>
Kinematic viscosity at 40 °C	ca. 22,0 mm <sup>2</sup> /s
Flash point (COC/DIN EN ISO 2592)	min. 140 °C
Pour point	< -5 °C
Copper corrosion (3 h/100 °C)	1 a - no fading

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E [info@gvg.nl](mailto:info@gvg.nl) - [www.gvg.nl](http://www.gvg.nl)

**AGEALUBE**<sup>®</sup>  
OIL FOR PROFESSIONALS