

Gear Oil UTTO BIO

Product Data Sheet | Art.no 4A23.06

Description

Bio-degradable, universal, hydraulic and transmission oil for systems of the most commonly-used agricultural and road-building machinery. Is suitable for oil-cooled hydraulic brake systems. For situations in which pollution of the environment is a realistic possibility and the operating temperature does not exceed 80°C.



Available in



1L



5L



20L



60L



208L

Typical standard analyses

Density at 15 °C, kg/l	0,903
Viscosity 40 °C, mm ² /s	46,50
Viscosity 100 °C, mm ² /s	10,00
Viscosity Index	211
Flash Point COC, °C	230
Pour Point, °C	-41
Total Base Number, mgKOH/g	4,7
Sulphate Ash, %	0,55

Performance level

Case MS1209/MS1207
CNH MAT 3525/MAT 3505
FNHA-2-C-201.00
Ford M2C134-D
John Deere J20C
Massey Ferguson M1145/M1143
Biodegradability according OECD 301 B > 60%

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms