

Hydra 46

Product Data Sheet | Art.no 4B0105

Description

Hydraulic oil suitable both for heavy-duty hydraulic systems and for low-workload gear transmission systems and bearings. Also highly suitable as circulation lubricant (with the exception of turbines) for vacuum pumps and for general machine lubrication. Do NOT use in systems with silver-plated components.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm²/s	46,00
Viscosity 100 °C, mm²/s	6,97
Viscosity Index	110
Flash Point COC, °C	215
Pour Point, °C	-30
Acid number, mgKOH/g	0,40
Sulphate Ash, %	0,06

Performance level

DIN 51524-2 HLP
AFNOR NF E 48-603 HM
ISO 11158 HM
ASTM D 6158 HM
Denison HF-0/HF-1/HF-2
Cincinnati Machine P-70
Eaton Brochure 694 for 35VQ25A
GM LS-2

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms