

# Hydra H 32

Product Data Sheet | Art.no 4B021.VG32

## Description

Hydraulic oil, suitable for intensively used systems in earth-moving equipment and fixed installations that have to operate under high pressure and over a high range of temperatures. Not for use in systems with silver-plated components.



## Available in



1L



5L



20L



60L



208L



Bulk

## Typical standard analyses

Density at 15 °C, g/ml	0.869
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	32.7
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	6.3
Viscosity index	147
Pour point, °C	-39
Flash Point COC, °C	204

## Performance level

AFNOR NF E 48-603 HV/690/691  
Cincinnati Machine P-68 (ISO 32)  
Denison HF-2  
DIN 51524-3  
Eaton Vickers I-286-S  
Eaton Vickers M-2950-S  
ISO 11158 HV  
ISO 6743-4 HV

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E [info@gvg.nl](mailto:info@gvg.nl) - [www.gvg.nl](http://www.gvg.nl)

**AGEALUBE**  
OIL FOR PROFESSIONALS