

# Multi Synth 10W40

Product Data Sheet | Art.no 4A06

## Description

A modern, semi-synthetic, fuel-saving engine oil. Suitable for all petrol and diesel engines, with or without turbo. Makes for a rapid cold start and is highly resistant to high temperatures. Meets the B4 requirement for direct-injection (turbo) diesels.



## Available in



1L



5L



20L



60L



208L



Bulk

## Typical standard analyses

|                            |       |
|----------------------------|-------|
| Density at 15 °C, kg/l     | 0,869 |
| Viscosity -25 °C, mPa.s    | 6170  |
| Viscosity 40 °C, mm²/s     | 90,00 |
| Viscosity 100 °C, mm²/s    | 13,50 |
| Viscosity Index            | 152   |
| Flash Point COC, °C        | 224   |
| Pour Point, °C             | -42   |
| Total Base Number, mgKOH/g | 10,2  |
| Sulphate Ash, %            | 1,29  |

## Performance level

|                    |
|--------------------|
| ACEA A3/B4-12      |
| API SL/CF          |
| MB 229.1           |
| VW 501.01 / 505.00 |

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E [info@gvg.nl](mailto:info@gvg.nl) - [www.gvg.nl](http://www.gvg.nl)

**AGEALUBE**  
OIL FOR PROFESSIONALS